



Appendix A | Bicycle Level of Traffic Stress Analysis Criteria

princeton bicycle master plan appendices | **2017**

Criteria for Level of Stress in Mixed Traffic

	Street Width		
Posted Speed Limit	2-3 Lanes	4-5 Lanes	6+
Up to 25 mph	LOS 1 or 2	LOS 3	LOS 4
30 mph	LOS 2 or 3	LOS 4	LOS 4
35+ mph	LOS 4	LOS 4	LOS 4

Level of Stress for Mixed Traffic in the Presence of a Right Turn Lane

Configuration	Level of Stress
Single right-turn lane with length ≤ 75 ft. and intersection angle and curb radius limit turning speed to 15 mph	(no effect on LOS)
Single right-turn lane with length between 75 and 150 ft., and intersection angle and curb radius limit turning speed to 15 mph	LOS ≥ 3
Otherwise	LOS = 4

Level of Stress for Unsignalized Crossings Without a Median Refuge

	Width of Street Being Crossed		
Speed Limit of Street Being Crossed	Up to 3 Lanes	4-5 Lanes	6+
Up to 25 mph	LOS 1	LOS 2	LOS 4
30 mph	LOS 1	LOS 2	LOS 4
30 mph	LOS 2	LOS 3	LOS 4
40+ mph	LOS 3	LOS 4	LOS 4

Source: Low-Stress Bicycling and Network Connectivity, Mineta Transportation Institute, 2012

Criteria for Bike Lanes Alongside a Parking Lane

	LTS ≥ 1	LTS ≥ 2	LTS ≥ 3	LTS ≥ 4
Street width (through lanes per direction)	2	(no effect)	4 or more	(no effect)
Sum of bike lane and parking lane width (includes marked buffer and paved gutter)	15 ft. or more	14 ft.	13.5 ft. or less	(no effect)
Speed limit or prevailing speed	25 mph or less	30 mph	35 mph	40 mph or more
Bike lane blockage (typically applies in commercial areas)	rare	(no effect)	frequent	(no effect)

Note: (no effect) = factor does not trigger an increase to this level of traffic stress

Criteria for Bike Lanes Not Alongside a Parking Lane

	LTS ≥ 1	LTS ≥ 2	LTS ≥ 3	LTS ≥ 4
Street width (through lanes per direction)	2	4, if directions are separated by a raised median	5, or 4 without a separating median	(no effect)
Bike lane width (includes marked buffer and paved gutter)	6 ft. or more	5.5 ft. or less	(no effect)	(no effect)
Speed limit or prevailing speed	30 mph or less	(no effect)	35 mph	40 mph or more
Bike lane blockage may apply in commercial areas)	rare	(no effect)	frequent	(no effect)

Note: (no effect) = factor does not trigger an increase to this level of traffic stress

Source: Low-Stress Bicycling and Network Connectivity, Mineta Transportation Institute, 2012

Volume Adjustment

Volume Threshold	Min. LTS
-	1
5,000	2
10,000	3
15,000	4

appendix a – bicycle level of traffic stress
princeton bicycle master plan | **2017**

